Product data sheet

DECORATIVE LIGHTING

V1-R0-9A403-30000-2004040 ENSO A 560X530X40 SUSPENDED 40W 4000K


VARTON



IP 20 IK 06

Input voltage (AC, 50Hz), V: 198...264 AC frequency, Hz: 50 Flicker, %: 5 Climatic modification and category of placement: УХЛ4 Protection class: I Housing material: Aluminium Mounting method: Pendant Ingress protection (IP): IP20 Impact resistance: IK06 Power factor: 0,95 https://www.varton.ru/products/interernoe-dekorativnoe-osveshchenie/enso-a/enso-a-560kh530kh40-podvesnye/svetilnik-varton-enso-a-560x530x40-mm-40-vt-cri90-4000-k-podvesnoy-ral9005-chernyy-matovyy-s-rasseiv_1/

Light output 1



1 x LED

Nominal lamp power	40 W	LOR	100%
Lamp flux	4200 lm	Total flux	4201 lm
Luminous efficacy	105 lm/W	Total power	40 W
CCT	4000 K		
CRI	90		

Mounting mode

Pendant

Shape and measurements

Length: 22.05 in
Width: 20.87 in
Height: 1.57 in

Adjustability

Fixed

Electric

System power: 40 W

Protection

IP: 20
IK: 06