


Product data sheet

ENTERO RD-S TRIMLESS IP SOFT 93045
28484 9030
DELTA LIGHT




Luminaire, ceiling recessed (indoor use) from Deltalight, named ENTERO RD-S TRIMLESS IP SOFT 93045, available in the colour(s): black, full white, gold coloured. For recessed mounting, a round opening (for installing a custom mounting kit) is needed and a min. depth for recessing of 115 mm. This luminaire is equipped with LED array 10,2W / CRI>90 (R9: 50) / 3000K-1800K / 1038lm with an optional driver, suitable for currents of 500mA. Light distributor: reflector 45°.


Light output 1



1 x LED			
Nominal lamp power	10.2 W	LOR	73%
Lamp flux	1038 lm	Total flux	755 lm
Luminous efficacy	102 lm/W	Total power	10.2 W
CCT	1800 K		
CRI	90		



1 x LED			
Nominal lamp power	10.2 W	LOR	73%
Lamp flux	1038 lm	Total flux	755 lm
Luminous efficacy	102 lm/W	Total power	10.2 W
CCT	1800 K		
CRI	90		



1 x LED			
Nominal lamp power	10.2 W	LOR	73%
Lamp flux	1038 lm	Total flux	755 lm
Luminous efficacy	102 lm/W	Total power	10.2 W
CCT	1800 K		
CRI	90		

Mounting mode

Ceiling recessed

Electric

System power: 10.2 W
Appliance Class: II

Shape and measurements

Height: 0.04 in

Diameter: 3.11 in

Weight: 0.245 kg

Protection

IP: 44

Designation labels: CE