


# Product data sheet

ECOLINE OFFICE 1200 WHITE 2450LM 4000K RA>80 DALI  
5703821176194  
SG ARMATUREN



Luminaire suspended/surface-mounted directly in 3000 or 4000 Kelvin LED. Flat design, powder-coated white RAL9010 gloss 25. Double parabolic reflector and diffuser with option of dimmable solution (DALI/SwitchDim). Plug-and-play solution for quick installation. Adjustable wire suspension (2x2 m) ordered as accessory. Light Distribution Direct Light technic LED 18W 4000K Ra>80 SDCM 3 L80/B10 >50.000 hrs Control/Dimming DALI Protection Class I IP20 Materials and finish Housing: Sheet steel Colour: White (Pure white, 25% gloss) Optics: Double parabolic louvre, satin matt, Aluminium Mounting/Connection Suspended or surface, Indoor Screwless terminal block Max. luminaires per circuit breaker: B10: 17, B16: 28, C10: 27, C16: 45

## Light output 1



1 x LED			
Nominal lamp power	18 W	LOR	100%
Lamp flux	2450 lm	ULOR	21%
Luminous efficacy	136 lm/W	Total flux	2451 lm
CCT	4000 K	Total power	18 W
CRI	80		

## Mounting mode

Ceiling mounted, Pendant

## Shape and measurements

Length: 47.24 in  
Width: 5.59 in  
Height: 2.48 in

## Adjustability

Fixed

## Design

Color of housing: White

## Electric

System power: 18 W  
Appliance Class: I

## Protection

IP: 20