# Product data sheet


LEEDS 1 SURFACE WALL LUMINAIRES
LEE-30031-T2-T4-W40
LIGMAN



IP 65 IK 07

- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000K - Die-cast aluminium housing and frame pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Through wiring on request for LEE-30011, LEE-30021, LEE-30041, LEE-30051 - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear toughened glass - Integral control gear

## Light output 1 (integrated)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 4000 K |
| Nominal lamp power | 15.3 W | CRI | 80 |
| Total flux | 1274 lm | LOR | 100% |
| Luminous efficacy | 83 lm/W | ULOR | 100% |
| | | Total power | 15.3 W |

### Mounting mode

Wall recessed

### Shape and measurements

Length: 4.02 in
Width: 3.74 in
Height: 3.15 in
Weight: 0.8 kg

### Adjustability

Fixed

### Design

Color of housing: Black, White, Silver gray

### Glare protection

Glare protection: UGR < 19

### Electric

System power: 15.3 W
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

### Protection

IP: 65
IK: 07
Surface temperature: 40°C