Product data sheet


ODESSA 5 FLOODLIGHTS,PROJECTORS
OD-50071-N-8040-A80121
LIGMAN



IP 66 IK 07

- Lamp COB - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency optical reflector - Clear toughened glass - Arm mounting installation - Integral control gear

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	19.9 W	CRI	80
Total flux	909 lm	LOR	100%
Luminous efficacy	46 lm/W	ULOR	50%
		Total power	19.9 W

Mounting mode

Standing / Bollard, Wall mounted

Shape and measurements

Height: 9.49 in
Diameter: 4.13 in
Weight: 3.1 kg

Adjustability

Free

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 19.9 W
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 66
IK: 07
Surface temperature: 40°C