



Product data sheet

RUBIN INDUSTRY SLIGHT LED 24000 OPTICS-2L SH IP65 E 34 840 / 1270X320MM HT45
19.4205.1421.34
LUXIONA



Indoor luminaire. Assembly: surface mounted on ceiling. The body material is steel sheet. Colour - RAL 9016 (white). Luminaire dimensions: 1270 x 320 x 55 mm. Diffuser: SH (transparent hardened glass). The efficiency of the optical system is 84,03%. Beam angle: (C0-C180) / (C90-C270) - 56,4° / 92,6°. Light source type: LED. Colour of the light 4000 K. SDCM=3. CRI>80. Lifetime of LED sources: 100000 (1) / 147000 (2) h L80/B10 (1) / L70/B50 (2). Luminaire luminous flux: 20999 lm. Power of luminaire: 171 W. Luminaire's light efficiency: 122,8 lm/W. Driver: standard on/off (E). Voltage 220..240 V, 50..60 Hz. Power factor cosφ: >0,95. Circuit load capacity: 14 (B10), 22 (B16), 14 (C10), 22 (C16). Operating temperature range: -25 ÷ 45° C. Protection degree: IP65. Impact resistant: IK08. Protection against electric shock: I.

Light output 1



6 x LED			
Nominal lamp power	28.5 W	LOR	83%
Lamp flux	4165 lm	Total flux	20858 lm
Luminous efficacy	146 lm/W	Total power	171 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 50.00 in
Width: 12.60 in
Height: 2.17 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 171 W
Appliance Class: I

Protection

IP: 65
IK: 08

Other operating numbers

Ambient temperature range: -13...113°F