

Product data sheet


FORTEBRACCIO FLUO WHITE + BASE
D33NFLU
LUCEPLAN




IP
20

Fortebraccio fissa nuovi parametri di efficienza e praticità per le lampade da lavoro. Lo snodo centrale permette ai due bracci di ruotare indipendentemente sull'asse orizzontale e verticale, garantendo grande fluidità di movimento anche in posizioni estreme e inconsuete. L'impugnatura in policarbonato consente di manovrare la lampada con semplicità e maneggevolezza.

Light output 1



1 x Compact fluorescent lamp			
Nominal lamp power	13 W	Socket	Gx24D-1
Lamp flux	900 lm	LOR	63%
Luminous efficacy	6 lm/W	Total flux	567 lm
CCT	3000 K	Total power	100 W
CRI	85		



1 x Halogen low voltage lamp without reflector			
Nominal lamp power	70 W	Socket	E27
Lamp flux	1200 lm	LOR	63%
Luminous efficacy	8 lm/W	Total flux	755 lm
CCT	3000 K	Total power	100 W
CRI	99		

Mounting mode

Standing / Bollard, Table luminaire

Shape and measurements

Length: 9.12 in
Width: 9.15 in
Height: 2.27 in

Adjustability

Rotatable, Tilttable

Electric

System power: 100 W

Information regarding emergency functions

Supplementary emergency lighting
Emergency sign: N/A

Protection

IP: 20