


Product data sheet

M1 - RECESSED - UGR<LT/>16 3000K CRI 90 4W CLD WHITE


22190101-39

DISANO



Housing: in steel plate. Optics: anti-glare for improved visual comfort. : UGR<lt/>19, according to standard EN 12464. Coating: epoxy polyester powder coating resistant to UV rays. Heat Sink: built-in. Low flicker: luminaire with very low flicker: evenly distributed light for greater visual safety. Photobiological risk: exempt risk group according to EN62471. : EN60598-1. With degree of protection according to EN60529. Equipment: galvanised steel wire springs for false ceiling mounting. On request: version with 15° or 30° beams. Available with different aesthetic finishes to create surprising lighting effects.

Light output 1



1 x LED

Nominal lamp power	4 W	LOR	100%
Lamp flux	194 lm	Total flux	194 lm
Luminous efficacy	48 lm/W	Total power	4 W
CCT	3000 K		
CRI	90		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 1.97 in

Width: 1.97 in

Height: 2.56 in

Adjustability

Fixed

Design

Material impression: Aluminum

Color of housing: White

Electric

System power: 4 W

Appliance Class: II

Protection

IP: 40

IK: 07

Designation labels: CE