


Product data sheet

MINI REO II OK 92737
19353 9230
DELTA LIGHT




Luminaire, ceiling recessed (indoor use) from Deltalight, named MINI REO II OK 92737, available in the colour(s): black, white. For recessed mounting, a round opening with a diameter of 70 mm is needed and a min. depth for recessing of 60 mm. This luminaire is equipped with LED array 5,8-8,6W / CRI>90 (R9: 60) / 2700K / 702-974lm with an optional driver, suitable for currents of 350mA to 500mA. Light distributor: reflector 37°.


Light output 1




1 x LED			
Nominal lamp power	9 W	LOR	73%
Lamp flux	974 lm	Total flux	709 lm
Luminous efficacy	108 lm/W	Total power	9 W
CCT	2700 K		
CRI	90		




1 x LED			
Nominal lamp power	8 W	LOR	73%
Lamp flux	885 lm	Total flux	644 lm
Luminous efficacy	111 lm/W	Total power	8 W
CCT	2700 K		
CRI	90		




1 x LED			
Nominal lamp power	6 W	LOR	73%
Lamp flux	702 lm	Total flux	511 lm
Luminous efficacy	117 lm/W	Total power	6 W
CCT	2700 K		
CRI	90		



1 x LED			
Nominal lamp power	8 W	LOR	73%
Lamp flux	885 lm	Total flux	644 lm
Luminous efficacy	111 lm/W	Total power	8 W
CCT	2700 K		
CRI	90		



1 x LED			
Nominal lamp power	6 W	LOR	73%
Lamp flux	702 lm	Total flux	511 lm
Luminous efficacy	117 lm/W	Total power	6 W
CCT	2700 K		
CRI	90		



1 x LED			
Nominal lamp power	9 W	LOR	73%
Lamp flux	974 lm	Total flux	709 lm
Luminous efficacy	108 lm/W	Total power	9 W
CCT	2700 K		
CRI	90		

Mounting mode

Ceiling recessed

Shape and measurements

Height: 0.08 in
Diameter: 3.03 in
Weight: 0.2 kg

Electric

System power: 6-9 W
Appliance Class: II

Protection

IP: 20
Designation labels: CE