


# Product data sheet

MINI REO II OK X 93037  
19354 9330  
DELTA LIGHT




Luminaire, ceiling recessed (indoor and outdoor use) from Deltalight, named MINI REO II OK X 93037, available in the colour(s): black, flemish bronze outdoor, anthracite (dark grey), white. For recessed mounting, a round opening with a diameter of 70 mm is needed and a min. depth for recessing of 60 mm. This luminaire is equipped with LED array 5,8-8,6W / CRI>90 (R9: 52) / 3000K / 734-1018lm with an optional driver, suitable for currents of 350mA to 500mA. Light distributor: reflector 37°.


## Light output 1




1 x LED			
Nominal lamp power	9 W	LOR	73%
Lamp flux	1018 lm	Total flux	741 lm
Luminous efficacy	113 lm/W	Total power	9 W
CCT	3000 K		
CRI	90		




1 x LED			
Nominal lamp power	6 W	LOR	73%
Lamp flux	734 lm	Total flux	534 lm
Luminous efficacy	122 lm/W	Total power	6 W
CCT	3000 K		
CRI	90		




1 x LED			
Nominal lamp power	9 W	LOR	73%
Lamp flux	1018 lm	Total flux	741 lm
Luminous efficacy	113 lm/W	Total power	9 W
CCT	3000 K		
CRI	90		



1 x LED			
Nominal lamp power	8 W	LOR	73%
Lamp flux	925 lm	Total flux	673 lm
Luminous efficacy	116 lm/W	Total power	8 W
CCT	3000 K		
CRI	90		



1 x LED			
Nominal lamp power	8 W	LOR	73%
Lamp flux	925 lm	Total flux	673 lm
Luminous efficacy	116 lm/W	Total power	8 W
CCT	3000 K		
CRI	90		



1 x LED			
Nominal lamp power	6 W	LOR	73%
Lamp flux	734 lm	Total flux	534 lm
Luminous efficacy	122 lm/W	Total power	6 W
CCT	3000 K		
CRI	90		

**Mounting mode**

Ceiling recessed

**Shape and measurements**

Height: 0.08 in  
Diameter: 3.03 in  
Weight: 0.2 kg

**Electric**

System power: 6-9 W  
Appliance Class: II

**Protection**

IP: 65  
Designation labels: CE