



Product data sheet

ARTSHAPE ROUND LED SMALL FULL SUSPENDED 6000 PLX E 34 840 / S-1,5M
19.4013.1321.34
LUXIONA



Indoor luminaire. Assembly: surface mounted on slings. The body material is aluminum. Colour - RAL 9016 (white). Luminaire dimensions: Ø650 x 85 mm. Weight 5,85 kg. Diffuser: PLX (PMMA opal). The efficiency of the optical system is 73,54%. Beam angle: (C0-C180) / (C90-C270) - 111,2° / 114,2°. Light source type: LED. Colour of the light 4000 K. SDCM=3. CRI>80. Lifetime of LED sources: 60000 h L80/B10. Luminaire luminous flux: 4377 lm. Power of luminaire: 47 W. Luminaire's light efficiency: 93,1 lm/W. Driver: standard on/off (E). Voltage 220..240 V, 50..60 Hz. Power factor cosp: >0,95. Circuit load capacity: 16 (B10), 26 (B16), 23 (C10), 37 (C16). Operating temperature range: 0 ÷ 30° C. Protection degree: IP20. Impact resistant: IK04. Protection against electric shock: I. Photobiological risk class (IEC/EN 62471): RG0. These luminaires are characterised by tightly closed chamber of LED light sources (IP65) thanks to this impurities are not visible on the diffuser for a long time of exploitation. Temperature range for storage and transport from 0° C to 40° C. The luminaire can be made in CLO (Constant Lumen Output) version. Please check in the data sheet and installation instructions whether installation accessories are required.

Light output 1



1 x LED			
Nominal lamp power	47 W	LOR	83%
Lamp flux	5952 lm	Total flux	4968 lm
Luminous efficacy	127 lm/W	Total power	47 W
CCT	4000 K		
CRI	80		

Mounting mode

Pendant

Shape and measurements

Height: 3.35 in
Diameter: 25.59 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 47 W
Appliance Class: I

Protection

IP: 20
IK: 04

Other operating numbers

Ambient temperature range: 32...86°F