



Product data sheet

CUT-4 LED 24 3500K DW
216330/3/DW/10KV
ROSA



Lighting set with a simple shape. Made of aluminium - the standard version is anodised in inox and grey. Designed to illuminate city roads and residential streets, office buildings' surroundings, parks and pedestrian routes. It has a protection class of IP 66 for the optical part and the power input system. The set is equipped with PMMA lenses and an interchangeable LED module. The expected service life of the product is L90B10 - 100,000 h. The input voltage frequency is 50/60Hz. Power factor ≥ 0.95 . Depending on the power variant, the set has: 12 LEDs (for 12W, 24 W, 36 W), 24 LEDs (for 48 W, 72 W). It is possible to connect the set to an external control system via the DALI interface (optional support for an analogue 1-10V signal).

Light output 1



1 x LED			
Nominal lamp power	28 W	LOR	82%
Lamp flux	4350 lm	Total flux	3568 lm
Luminous efficacy	155 lm/W	Total power	28 W
CCT	3500 K		
CRI	70		

Mounting mode

Pole integrated, Pole top mounted

Shape and measurements

Length: 31.50 in
Width: 5.91 in
Height: 3.74 in

Adjustability

Fixed

Electric

System power: 28 W

Protection

IP: 66