

Product data sheet

TRIANGLE 6 STREET AND AREA LIGHTING LUMINAIRES


TR-96151-M-W40

LIGMAN




- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear toughened glass - Surge protection 10 kV

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	37.5 W	CRI	80
Total flux	4859 lm	LOR	100%
Luminous efficacy	130 lm/W	Total power	37.5 W

Light output 2 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	37.5 W	CRI	80
Total flux	4859 lm	LOR	100%
Luminous efficacy	130 lm/W	Total power	37.5 W

Mounting mode

Wall mounted, Pole top mounted

Shape and measurements

Length: 49.37 in

Width: 23.62 in

Height: 20.24 in

Weight: 18 kg

Adjustability

Fixed

Glare protection

Glare protection: UGR < 19

Electric

System power: 75 W

Voltage: 230 V AC

Ballast: ECG

Controller: Dimmable 1..10V, DALI

Appliance Class: I

Design

Color of housing: Black, White, Silver gray

Protection

IP: 54

IK: 07

Surface temperature: 40°C