
Product data sheet


PLAY FLAT ROUND FIXED EMERGENCY
AG11-P7V9M2O314
LEDSC4



IP 54 IK 03


LedsC4 Play Flat Round Fixed Emergency AG11-P7V9M2O314 Downlight For downlighting. Structure material: Aluminium. Structure finish: White. Diffuser material: Methacrylate. Diffuser finish: Transparent. Warranty: 5 Years. Product net weight (Kg): 0.69 Product width or diameter (mm): 65 Product height (mm): 67 Ø of the hole for recessing (mm): 58 Permitted ceiling thickness: 0-7 Class 2. Luminaire not suitable for coating with insulation materials. Glow wire test: 850. IP: IP54. IK: IK03. LED. No. of lampholders or LEDs: 1. LED brand: CREE. Driver brand: VOSSLOH-SCHWABE. Maximum power of light source: 6.4W. Colour temperature: 2700K. Colour rendering index: 90. MacAdam Steps: 2. Hours of life: 50.000h L80B20. UGR: 16. Photobiological risk: RG1. Real flux (lm): 582. Real lm/W: 68. Voltage / frequency range: 100-240/50-60Hz. Voltage: 9. Equipment included: Yes. Total power: 8.5. Power factor: 0.90. Dimmable equipment included: ON-OFF. Emergency supply provision.

Light output 1 (emergency)



1 x LED

Nominal lamp power	2.13 W	LOR	100%
Lamp flux	146 lm	Total flux	146 lm
Luminous efficacy	68 lm/W	Total power	2.13 W
CCT	2700 K		
CRI	90		



1 x LED

Nominal lamp power	8.5 W	LOR	100%
Lamp flux	582 lm	Total flux	582 lm
Luminous efficacy	68 lm/W	Total power	8.5 W
CCT	2700 K		
CRI	90		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 2.56 in
Width: 2.56 in
Height: 0.08 in

Electric

System power: 2.13-8.5 W
Appliance Class: II

Information regarding emergency functions

Emergency lighting only
Emergency sign: N/A

Adjustability

Fixed

Protection

IP: 54

IK: 03