


# Product data sheet

EVA III  
9.751.3062.00  
LEIPZIGER LEUCHTEN



For medium light requirements, mounting height 4.50 - 6.00 m. - Impact-resistant beaded polycarbonate attachment, UV-stabilized - Aluminium reflector finished in special white paint for max. light reflection - Corrosion-resistant cast aluminium unit carrier, painted - All electrical components on a block - Adapter jack for connection - Available in any RAL- or DB -colour without surcharge - For concrete pole with flange plate made of hot galvanized steel Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711

### Light output 1



1 x High pressure mercury vapour lamp			
Nominal lamp power	125 W	LOR	83%
Lamp flux	6800 lm	ULOR	22%
Luminous efficacy	41 lm/W	Total flux	5672 lm
CCT	3400 K	Total power	137 W
CRI	54		

### Mounting mode

Pole top mounted

### Shape and measurements

Height: 17.72 in  
Diameter: 15.75 in

### Design

Material impression: Gloss

### Electric

System power: 137 W  
Ballast: ECG  
Suitable for feed-through wiring

### Protection

IP: 55  
Designation labels: CE

### Other operating numbers

Ambient temperature range: 32...86°F