

Product data sheet

SMART CAKE 160 DIFFUSE IP55 LED GE 3000K WIDE FLOOD WHITE STRUC


13005109

MODULAR




Soft light Smart cake is part of the Smart family. This family's styling is based on our most popular iconic designs. Its gently sloping sides ensure a soft distribution of light. Since its introduction in 2010, Smart has become an extensive portfolio with a broad range of accessories. Concretely this means that the luminaires consist of a light source (LED, halogen), which can be combined with one of three trims to suit your needs. The new spotlights can be combined with Smart mask, Smart surface box or surface tubed to form the perfect solution for any interior. Choose a white, black or gold finishing. Also available in different sizes, fix and adjustable, IP version, ...

Light output 1




1 x LED

Nominal lamp power	30.8 W	LOR	69%
Lamp flux	3541 lm	Total flux	2427 lm
Luminous efficacy	79 lm/W	Total power	30.8 W
CCT	3000 K		
CRI	90		




1 x LED

Nominal lamp power	23.5 W	LOR	69%
Lamp flux	2853 lm	Total flux	1955 lm
Luminous efficacy	83 lm/W	Total power	23.5 W
CCT	3000 K		
CRI	90		




1 x LED

Nominal lamp power	16 W	LOR	69%
Lamp flux	2095 lm	Total flux	1436 lm
Luminous efficacy	90 lm/W	Total power	16 W
CCT	3000 K		
CRI	90		




1 x LED

Nominal lamp power	49.7 W	LOR	69%
Lamp flux	5296 lm	Total flux	3630 lm
Luminous efficacy	73 lm/W	Total power	49.7 W
CCT	3000 K		
CRI	90		



1 x LED

Nominal lamp power	36.3 W	LOR	69%
Lamp flux	4095 lm	Total flux	2806 lm
Luminous efficacy	77 lm/W	Total power	36.3 W
CCT	3000 K		
CRI	90		



1 x LED

Nominal lamp power	42 W	LOR	69%
Lamp flux	4600 lm	Total flux	3153 lm
Luminous efficacy	75 lm/W	Total power	42 W
CCT	3000 K		
CRI	90		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 6.30 in

Width: 6.30 in

Height: 4.76 in

Weight: 0.98 kg

Adjustability

Fixed

Electric

System power: 16-49.7 W

Appliance Class: II

Protection

IP: 55