



Product data sheet

RUBIN LOOK LED 3900 PLX E 34 830 / 600X600
19.4360.7411.34
LUXIONA



Indoor luminaire. Assembly: surface mounted on ceiling. The body material is steel sheet. Colour - RAL 9016 (white). Luminaire dimensions: 595 x 595 x 55 mm. Weight 4,1 kg. Diffuser: PLX (PMMA opal). The efficiency of the optical system is 73,03%. Beam angle: (C0-C180) / (C90-C270) - 102,8° / 102,8°. Light source type: LED. Colour of the light 3000 K. SDCM=3. CRI>80. Lifetime of LED sources: 100000 (1) / 147000 (2) h L80/B10 (1) / L70/B50 (2). Luminaire luminous flux: 2766 lm. Power of luminaire: 21,7 W. Luminaire's light efficiency: 127,5 lm/W. Driver: standard on/off (E). Voltage 220..240 V, 50..60 Hz. Power factor cosφ: >0,95. Circuit load capacity: 30 (B10), 48 (B16), 43 (C10), 70 (C16). Operating temperature range: 5 ÷ 30° C. Protection degree: IP40. Impact resistant: IK04. Protection against electric shock: I. Photobiological risk class (IEC/EN 62471): RG0.

Light output 1



3 x LED			
Nominal lamp power	7.233 W	LOR	83%
Lamp flux	1263 lm	Total flux	3162 lm
Luminous efficacy	175 lm/W	Total power	21.7 W
CCT	3000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 23.43 in
Width: 23.43 in
Height: 2.17 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 21.7 W
Appliance Class: I

Protection

IP: 40
IK: 04

Other operating numbers

Ambient temperature range: 41...86°F