


# Product data sheet

KTRIBE F1 CRO/ALL.ARG.  
F6265004  
FLOS



Floor lamp providing diffused lighting; a switch located near the diffuser allows for 4-level light adjustment via a "remote" dimmer positioned on the power cord near the plug. Base and rod support in die-cast, polished Zamak alloy. Rod, arm support, arm and diffuser support in polished aluminum tube. Molded steel counterweight with galvanized finish. Injection-molded PC (polycarbonate) inner diffuser opal color. Outer in transparent PMMA (polymethylmethacrylate), silver or bronze on the inner surface, by vacuum aluminum coating. Injection-molded PC (polycarbonate) upper ring, completely transparent, or transparent brown for the outer bronze diffuser. FEP/PVC, UV-stabilized transparent power cord length 1500 mm. Net weight 4,3 kg.

## Light output 1



### 1 x Halogen low voltage lamp without reflector

Nominal lamp power	70 W	Socket	E27
Lamp flux	1240 lm	LOR	16%
Luminous efficacy	3 lm/W	ULOR	8%
CCT	2800 K	Total flux	202 lm
CRI	99	Total power	70 W

## Mounting mode

Standing / Bollard, Floor mounted

## Shape and measurements

Length: 9.84 in

Width: 9.84 in

Height: 34.45 in

## Adjustability

Rotatable

## Electric

System power: 70 W

## Protection

IP: 20