



Product data sheet

1622 STARLED - ROUND 4000K CRI 80 0.6W CLD-S+L GRAPHITE
530690-00
DISANO



Housing: in glass sphere nylon, shatterproof, frame in die-cast aluminium. Diffuser: matt glass, resistant to thermal shock and impact (UNI EN 12150-1:2001). Coating: pre-treatment of metal surface, polyester powder coating to ensure resistance to corrosion and salt spray fogs, UV stabilised. Wiring: power supply 220-240V 50/60Hz with external transformer acc. 179. Cable with insulation class 3. Photobiological risk: exempt risk group according to EN62471. : EN60598-1. With degree of protection according to EN60529. Laboratory tests: the luminaire passed the static load resistance test (EN 60598-2-13) with an applied weight of 40KN equal to 2000 kg. Equipment: silicone and EPDM rubber sealing gasket. Warnings: driveway lamp. Keep clear.

Light output 1



1 x LED			
Nominal lamp power	0.6 W	LOR	100%
Lamp flux	28 lm	Total flux	28 lm
Luminous efficacy	47 lm/W	Total power	0.6 W
CCT	4000 K		
CRI	80		

Mounting mode

Wall recessed

Shape and measurements

Length: 3.74 in
Width: 3.74 in
Height: 3.43 in

Adjustability

Fixed

Design

Color of housing: Anthracite / graphite

Electric

System power: 0.6 W
Appliance Class: III

Protection

IP: 67
IK: 08
Designation labels: CE