
Product data sheet


TRIONA PRISMATIK
312300.0031.76
RZB



IP 20 IK 03

Series: Triona Type of Protection: IP 20 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Halterung und Leuchtenrahmen Metall pulverbeschichtet. Diffusorsegmente (Lichtaustritt indirekt) aus vergilbungsfreiem Kunststoff (PMMA) opal. Diffusor (Lichtaustritt direkt) aus Kunststoff (PMMA) opal / mikroprismatisch. Betriebsgerät eingebaut. Leuchtmittel (LED) im Lieferumfang enthalten. Available Colours: anthracite metallic Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 845, H 88 Lamp: LED Life time: 50000 h (L70/B10) Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Converter, dimmable, DALI Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 10000lm System power: 110W Beam Angle: 95° Number of fittings B10A: 4 Number of fittings B16A: 7 Inrush current: 73A Unified Glare Ratio: 16,7 EEC: A++

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	110.3 W	CRI	80
Total flux	8650 lm	LOR	100%
Luminous efficacy	78 lm/W	ULOR	30%
		Total power	110.3 W

Mounting mode

Wall mounted

Shape and measurements

Height: 2.05 in
Diameter: 33.27 in

Adjustability

Fixed

Electric

System power: 110.3 W

Protection

IP: 20
IK: 03