
Product data sheet

LUCAS IV (WALL FITTING) 9.834.3066.15 LEIPZIGER LEUCHTEN






CCT

CRI

Mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets -Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1




1 x High pressure mercury vapour lamp				
Nominal lamp power	125 W	LOR		
Lamp flux	6800 lm	Total flux		
Luminous efficacy	42 lm/W	Total powe		

3400 K

54

LOR	84%
Total flux	5697 lm
Total power	137 W



1 x High pressure mercury vapour lam	n

Nominal lamp power	80 W	LOR	84%
Lamp flux	4000 lm	Total flux	3351 lm
Luminous efficacy	38 lm/W	Total power	89 W
CCT	3400 K		
CRI	54		

Mounting mode	Electric
Wall mounted	System power: 89-137 W
Shape and measurements	Ballast: ECG
Height: 22.44 in	Protection
Diameter: 22.44 in	IP: 55
Design	Designation labels: CE
Material impression: Matt	Other operating numbers
Color of housing: White	Ambient temperature range: -495°F