Product data sheet

GEORG V (1-ARMED) 9.870.0128.04

LEIPZIGER LEUCHTEN









With mounting heights between 3.00 and 4.00 m for medium and low light requirements. - Large shade, inside in special white paint for better reflection - Luminaire body made of aluminium/galvanized steel sheet, outside painted in colour, inside finished in special white pain - Impact-resistant polyethylene attachment rotates and locks into place for easy lamp replacement - Steel tubing galvanized and painted -Wired ready for connection - Connection by adapter jack -Available in any RAL or DB colour without surcharge -Order pole for single-bracket luminaire, dia. 60 mm,and pole for multi-bracket luminaire, dia. 76 mm,separately Voltage: 230V 50Hz Protected to: IP 54 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x High pressure sodium vapour lamp		
Nominal lamp power	50 W	LOR
Lamp flux	3500 lm	ULOR
Luminous efficacy	41 lm/W	Total flux
CCT	2000 K	Total power
CRI	25	



1 x High pressure sodium vapour lamp Nominal lamp power 70 W LOR 72% Lamp flux 5600 lm **ULOR** 4% 48 lm/W Total flux Luminous efficacy 4025 lm CCT 2000 K Total power 83 W CRI 25

Mounting mode

Pole top mounted

Shape and measurements

Height: 28.35 in Diameter: 22.83 in Electric

System power: 62-83 W

Protection

IP: 54

72% 4% 2515 lm 62 W