# Product data sheet


LYCKSELE 1 LIGHT COLUMNS
LY-20001-W-W40
LIGMAN



IP 66 IK 08


- Lamp COB - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000K - Life time L90B10 Ta 25° 50,700 - Life time L80B10 Ta 50° > 63,500 - Die-cast aluminium housing, extruded aluminium column and arm pre-treated before powder coating ensuring high corrosion resistance - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear toughened glass - Maximum wind load resistance is 140 km/h - Surge protection 10kV

## Light output 1 (integrated)




| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 4032 K |
| Nominal lamp power | 36.8 W | CRI | 80 |
| Total flux | 3218 lm | LOR | 100% |
| Luminous efficacy | 87 lm/W | Total power | 36.8 W |

## Light output 2 (integrated)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 4032 K |
| Nominal lamp power | 36.8 W | CRI | 80 |
| Total flux | 3218 lm | LOR | 100% |
| Luminous efficacy | 87 lm/W | Total power | 36.8 W |

## Light output 3 (integrated)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 4032 K |
| Nominal lamp power | 36.8 W | CRI | 80 |
| Total flux | 3218 lm | LOR | 100% |
| Luminous efficacy | 87 lm/W | Total power | 36.8 W |

### Mounting mode

Standing / Bollard, Pole top mounted

### Shape and measurements

Height: 279.72 in
Diameter: 5.12 in
Weight: 68.3 kg

### Adjustability

Free

### Design

Color of housing: Black, White, Silver gray

### Glare protection

Glare protection: UGR < 19

### Electric

System power: 110.4 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

### Protection

IP: 66
IK: 08
Surface temperature: 40°C