


Product data sheet

IP65 T5 2X35/49 TETT INDUSTRI
5703708350747
SOLAR




IP65 En enkel og robust armatur, kan brukes til en rekke områder hvor fuktigheten eller støv forekommer. Armaturen kan monteres direkte i taket, på "klikk-on" opphengs braketten eller i wire. Armaturen leveres som standard med elektronisk ballast og rustfrie stål klips. Armaturhuset er i glassfiberarmert polysester. Bunnprofil i hvitlakkert stålplate, Avskjerming i sprøytetøpt støpt akryl. (PMMA). Solar Pluss

Light output 1




2 x Fluorescent lamp tubular T5

Nominal lamp power	49 W	Socket	G5
Lamp flux	4300 lm	LOR	69%
Luminous efficacy	54 lm/W	ULOR	8%
CCT	4000 K	Total flux	5958 lm
CRI	85	Total power	111 W




2 x Fluorescent lamp tubular T5

Nominal lamp power	49 W	Socket	G5
Lamp flux	4300 lm	LOR	69%
Luminous efficacy	54 lm/W	ULOR	8%
CCT	3000 K	Total flux	5958 lm
CRI	85	Total power	111 W



2 x Fluorescent lamp tubular T5

Nominal lamp power	35 W	Socket	G5
Lamp flux	3300 lm	LOR	69%
Luminous efficacy	41 lm/W	ULOR	8%
CCT	4000 K	Total flux	4572 lm
CRI	85	Total power	111 W



2 x Fluorescent lamp tubular T5

Nominal lamp power	35 W	Socket	G5
Lamp flux	3300 lm	LOR	69%
Luminous efficacy	41 lm/W	ULOR	8%
CCT	3000 K	Total flux	4572 lm
CRI	85	Total power	111 W

Mounting mode

Ceiling mounted

Electric

System power: 111 W

Shape and measurements

Length: 62.60 in

Width: 6.69 in

Height: 4.72 in

Protection

IP: 65

Adjustability

Fixed