
Product data sheet

M26L - SPY 39 FRAMER 927 DIM5
23432 9205
DELTA LIGHT




Luminaire, low voltage systems low voltage system mounted (indoor use) from Deltalight, named M26L - SPY 39 FRAMER 927 DIM5, available in the colour(s): black. This luminaire can be used with the following 48V magnetic lighting system(s): SHIFTLINE M26L - PROFILE. This luminaire is equipped with LED array 8,6W / CRI>90 (R9: 60) / 2700K / 974lm with build-in converter to operate on a voltage of 48V-DC. Dimming protocol: DALI. Light distributor: lens.

Light output 1




1 x LED

Nominal lamp power	9 W	LOR	73%
Lamp flux	974 lm	Total flux	709 lm
Luminous efficacy	108 lm/W	Total power	9 W
CCT	2700 K		
CRI	90		




1 x LED

Nominal lamp power	9 W	LOR	73%
Lamp flux	974 lm	Total flux	709 lm
Luminous efficacy	108 lm/W	Total power	9 W
CCT	2700 K		
CRI	90		



1 x LED

Nominal lamp power	9 W	LOR	73%
Lamp flux	974 lm	Total flux	709 lm
Luminous efficacy	108 lm/W	Total power	9 W
CCT	2700 K		
CRI	90		



1 x LED

Nominal lamp power	9 W	LOR	73%
Lamp flux	974 lm	Total flux	709 lm
Luminous efficacy	108 lm/W	Total power	9 W
CCT	2700 K		
CRI	90		

Mounting mode

Ceiling mounted, Pendant, Contact rail, Wall mounted

Shape and measurements

Length: 0.79 in
Width: 6.69 in
Height: 0.04 in

Electric

System power: 9 W
Appliance Class: II

Protection

IP: 20
Designation labels: CE