


Product data sheet

LD48 1.6W 500MA MB
LD48-C1-500-MB
LIGHTGRAPHIX



LD48 Ø63mm Recessed Wall Light. Constant Current. 1.6W 500mA 31° Medium beam. The LD48 has been updated with the latest LED technology and fitted with our new optics. The lens assembly is recessed and inclined by 20° for a floor wash illumination with minimal glare. This is a high-quality fitting with a machined 316 stainless steel bezel and black anodized body, for interior and exterior use. It has no visible fixings and the glass is fixed with a hidden gasket, so no unsightly glue line is visible. A choice of beam angles and colour temperatures are available.

Light output 1 (integrated)



| | | | |
|--------------------|---------|-------------|--------|
| Lamp type | LED | CCT | 3000 K |
| Nominal lamp power | 1.6 W | CRI | 93 |
| Total flux | 138 lm | LOR | 100% |
| Luminous efficacy | 86 lm/W | Total power | 1.6 W |

Mounting mode

Wall recessed

Shape and measurements

Height: 1.50 in
Diameter: 2.48 in

Adjustability

Fixed

Design

Material impression: Matt, Bronze, Glass, Brass, Gloss, Stainless steel
Color of housing: Black, White, Anthracite / graphite, Silver gray

Electric

System power: 1.6 W
Controller: Dimmable 0..10V, Dimmable 1..10V, DMX, DALI
Appliance Class: III

Protection

IP: 67
Designation labels: CE

Other operating numbers

Ambient temperature range: -4...95°F