

Product data sheet


LIGHT EYE® 90
1008169
SLV




IP
20

The popular spotlights and pendant lights for the 1- and 3-phase system extend the LIGHT EYE® family with new elegant models. Available in diameters of 90 and 150 mm, they offer a stylish design that shines with a sophisticated matt look. The separately available and interchangeable decorative rings create a modern look with their trendy colours.


Light output 1



1 x LED			
Nominal lamp power	6 W	Socket	Gu10
Lamp flux	450 lm	LOR	87%
Luminous efficacy	65 lm/W	ULOR	44%
CCT	4033 K	Total flux	392 lm
CRI	93	Total power	6 W



1 x LED			
Nominal lamp power	6 W	Socket	Gu10
Lamp flux	450 lm	LOR	87%
Luminous efficacy	65 lm/W	ULOR	44%
CCT	2723 K	Total flux	392 lm
CRI	92	Total power	6 W



1 x LED			
Nominal lamp power	6 W	Socket	Gu10
Lamp flux	450 lm	LOR	87%
Luminous efficacy	65 lm/W	ULOR	44%
CCT	3058 K	Total flux	392 lm
CRI	92	Total power	6 W

Mounting mode

Ceiling mounted, Contact rail

Electric

System power: 6 W

Shape and measurements

Length: 39.37 in

Width: 39.37 in

Height: 39.37 in

Weight: 0.272 kg

Adjustability

Fixed

Protection

IP: 20