


# Product data sheet

ICON 44 LED HELDER F4T1  
4481X4XX  
PROLUMIA




Light Source: Philips LumiLEDs Luxeon TX Color temperature: 3000K / 4000K Color rendering index: Ra ≥ 75 Operating temperature: -30°C ~ +50°C Rated life hours: L90 > 100.000 hours LED driver (included): Meanwell / Philips Xitanium Input: 220-240V AC 50/60Hz Power factor: > 0,95

## Light output 1




### 1 x LED

Nominal lamp power	70 W	LOR	100%
Lamp flux	5800 lm	Total flux	5800 lm
Luminous efficacy	83 lm/W	Total power	70 W
CCT	4000 K		
CRI	80		




### 1 x LED

Nominal lamp power	55 W	LOR	100%
Lamp flux	4800 lm	Total flux	4800 lm
Luminous efficacy	87 lm/W	Total power	55 W
CCT	4000 K		
CRI	80		



### 1 x LED


Nominal lamp power	70 W	LOR	100%
Lamp flux	5800 lm	Total flux	5800 lm
Luminous efficacy	83 lm/W	Total power	70 W
CCT	3000 K		
CRI	80		



**1 x LED**

Nominal lamp power	55 W
Lamp flux	4800 lm
Luminous efficacy	87 lm/W
CCT	3000 K
CRI	80


LOR	100%
Total flux	4800 lm
Total power	55 W



**1 x LED**

Nominal lamp power	47 W
Lamp flux	4200 lm
Luminous efficacy	89 lm/W
CCT	4000 K
CRI	80


LOR	100%
Total flux	4200 lm
Total power	47 W



**1 x LED**

Nominal lamp power	47 W
Lamp flux	4200 lm
Luminous efficacy	89 lm/W
CCT	3000 K
CRI	80


LOR	100%
Total flux	4200 lm
Total power	47 W



**1 x LED**

Nominal lamp power	42 W
Lamp flux	3800 lm
Luminous efficacy	90 lm/W
CCT	4000 K
CRI	80


LOR	100%
Total flux	3800 lm
Total power	42 W



**1 x LED**


Nominal lamp power	42 W
Lamp flux	3800 lm
Luminous efficacy	90 lm/W
CCT	3000 K
CRI	80

LOR	100%
Total flux	3800 lm
Total power	42 W



**1 x LED**

Nominal lamp power	34 W	LOR	100%
Lamp flux	3200 lm	Total flux	3200 lm
Luminous efficacy	94 lm/W	Total power	34 W
CCT	4000 K		
CRI	80		



**1 x LED**

Nominal lamp power	34 W	LOR	100%
Lamp flux	3200 lm	Total flux	3200 lm
Luminous efficacy	94 lm/W	Total power	34 W
CCT	3000 K		
CRI	80		

**Mounting mode**

Ceiling mounted, Pole top mounted

**Shape and measurements**

Height: 10.83 in

Diameter: 22.48 in

**Electric**

System power: 34-70 W

Appliance Class: 0

**Protection**

IP: 66

IK: 08

Designation labels: CE