


# Product data sheet

QUADRANA ÖKO  
311516.004  
RZB




IP  
40

IK  
05

Series: Quadrana Type of Protection: IP 40 Protection Class: I Voltage: 230 V / 50 Hz Base: die-cast aluminium, powder-coated. Diffuser fastening: toggles. Diffuser: plastic (PMMA), opal. Front: transparent, prismatic inside. With Gore-TM Protective Vents membrane valve as standard. Available Colours: silver, metallic Type of Installation: Ceiling mounting, Wall (surface) Dimensions: L 300, B 300, H 115 Lamp: LED Colour Temperature: 6300K Socket 1: without socket Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK05 (0,70 Joule) Luminaire flux LED: 650lm System power: 16W Beam Angle: 86° Unified Glare Ratio: 12,2 EEC: A+

## Light output 1 (integrated)



Lamp type	LED	CCT	6300 K
Nominal lamp power	16 W	CRI	60
Total flux	650 lm	LOR	100%
Luminous efficacy	41 lm/W	ULOR	29%
		Total power	16 W

## Mounting mode

Wall mounted

## Shape and measurements

Length: 11.81 in  
Width: 11.81 in  
Height: 4.53 in

## Adjustability

Fixed

## Electric

System power: 16 W

## Protection

IP: 40  
IK: 05