
Product data sheet


PANEL COMPACT 600 26W 840
4099854734489
LEDVANCE



IP 50 IK 02

Square recessed panel luminaires, 600 x 600 mm. Product features: Extruded aluminum frame, metal housing. Polystyrene diffuser. Lifetime (L80/B10): up to 75,000 h (at 25 °C). 3-pole terminal block, cable cross section up to 3 x 1.5 mm². Type of protection: IP50 (panel luminaire), IP20 (driver). Product benefits: Energy savings thanks to high system efficacy: up to 140 lm/W. High color consistency with SDCM 3. Through-wiring possible. Decentral emergency lighting possible with separately available LEDVANCE Emergency Conversion Box. Versions with reduced glare (U19) for office applications available. Areas of application: Suitable for recessed ceiling systems with grid size of 600 x 600 mm. Direct replacement for luminaires with fluorescent lamps. Offices, conference rooms. Reception areas, foyers, corridors, elevators. Equipment / Accessories: Accessories for several mounting options available. Security rope for luminaire included. Security brackets preinstalled. External control gear included. Suitable for use with separate Emergency Conversion Box. Replacement driver separately available. Safety advice: All electrical connections must be made by a qualified person.. The external flexible cable or cord of this luminaire cannot be replaced; if the cord is damaged, the luminaire must be disposed of.. Caution, risk of electric shock.. The luminaires are not suitable for covering with thermally insulated material..

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	26 W	CRI	80
Total flux	3640 lm	LOR	100%
Luminous efficacy	140 lm/W	ULOR	6%
		Total power	26 W

Mounting mode

Ceiling mounted, Pendant

Shape and measurements

Length: 23.43 in
Width: 23.43 in
Height: 1.34 in
Weight: 1.45 kg

Adjustability

Fixed

Design

Material impression: Aluminum
Color of housing: White

Electric

System power: 26 W
Appliance Class: II

Protection

IP: 50
IK: 02
Designation labels: CE, ENEC

Other operating numbers

Ambient temperature range: 14...113°F