Product data sheet


ECLFWVW
ECLFWVW_FULL_PRL1530DEG_MIN ZOOM
PROLIGHTS



IP 20 IK 08

EclProfile FWVW is the Variable White version of the new generation of Ecl Profile LED ellipsoidals, offering linear CCT control from 2,700 K to 5,600 K. The EclProfile FWVW has been engineered in the same housing and optical design of the colour mixing versions and for those users who require higher brightness and quality on whites, offering a superior evenness and crisp focus of the new EclProfile range. The LED source has been selected to achieve the finest quality of whites, having high scores of CRI, R9 and TM30 and being ideal for applications like corporate events, advertising, exhibitions, among others. Features: Linear CCT control 2,700 K - 5,600 K. High lumen output and superior quality of whites (high CRI, TLCI, TM30). Silent operation and compatible with industry standard accessories.

Light output 1



1 x LED

Nominal lamp power	259.3 W	LOR	100%
Lamp flux	6509 lm	Total flux	6522 lm
Luminous efficacy	25 lm/W	Total power	265 W
CCT	3945 K		
CRI	95		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 7.95 in
Width: 1.26 in
Height: 13.98 in

Adjustability

Rotatable, Free

Electric

System power: 265 W
Controller: DMX
Color adjustable
Appliance Class: I

Protection

IP: 20
IK: 08
Surface temperature: 70°C
Designation labels: CE