
Product data sheet

CAELA QMS LED1200-827 OP WH WH APWH
62907573
ZUMTOBEL



Pendant LED luminaire (square) with variable luminaire body for architectural structures (e.g. arches, waves); luminaire ultra-flat with integrated converter; modular LED luminaire concept; cover of polymethylmethacrylate (PMMA), opal with symmetric Lambertian light distribution; lamp(s): 1/13W LED1200-827; Colour rendering Ra > 80, colour temperature 2700 K (warm white); Chromaticity tolerance (initial MacAdam): 3; Luminaire luminous flux: 1200 lm, Luminaire efficacy: 92 lm/W; service life: 50000 h for luminous flux at 90%; control gear: LED converter ; luminaire unit can be rotated through 355°and tilted through ±30°; luminaire consists of housing, cover and trim; housing of die-cast aluminium, white matt painted; trim in polycarbonate, white; Suspension consists of pre-assembled cable (2000 mm) and included white ceiling rose (pendant tube must be ordered separately); electrical connection: 5-pole connector terminal, through-wiring is not possible; total power: 13 W; mains voltage: 220-240V/ 50/60Hz; class of protection I; dimensions: 331 x 331 x 74 mm; weight: 3.8 kg; Note: please order pendant tube separately. Can be cut to length on-site.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	13 W	CRI	80
Total flux	1200 lm	LOR	100%
Luminous efficacy	92 lm/W	Total power	13 W

Mounting mode

Pendant

Shape and measurements

Length: 13.03 in
Width: 13.03 in
Height: 2.91 in
Weight: 3.8 kg

Design

Material impression: Aluminum
Color of housing: White

Electric

System power: 13 W
Voltage: 220-240 V AC
Appliance Class: I

Protection

IP: 20
Designation labels: CE