


Product data sheet

ENOLA
149388
SLV




The ENOLA pendant is made from aluminium and shaped like a cylinder facing downwards. Thanks to the variety of housing colours, the ENOLA pendant offers combined installation possibilities. This gives the customer options for individual and colourful arrangements. Equipped with an E27 socket for incandescent or energy-saving lamps, ENOLA pendant is powered directly from 230V mains.

Light output 1




1 x Compact fluorescent lamp

Nominal lamp power	13.5 W	Socket	E27
Lamp flux	1520 lm	LOR	7%
Luminous efficacy	5 lm/W	Total flux	110 lm
CCT	3058 K	Total power	24 W
CRI	92		




1 x Compact fluorescent lamp

Nominal lamp power	8 W	Socket	E27
Lamp flux	880 lm	LOR	7%
Luminous efficacy	5 lm/W	Total flux	64 lm
CCT	3058 K	Total power	14 W
CRI	92		



1 x Compact fluorescent lamp

Nominal lamp power	8 W	Socket	E27
Lamp flux	880 lm	LOR	7%
Luminous efficacy	6 lm/W	Total flux	64 lm
CCT	4033 K	Total power	11 W
CRI	92		



1 x Halogen low voltage lamp without reflector

Nominal lamp power	7.5 W	Socket	E27
Lamp flux	700 lm	LOR	7%
Luminous efficacy	7 lm/W	Total flux	51 lm
CCT	2723 K	Total power	7.5 W
CRI	90		

Mounting mode

Pendant

Shape and measurements

Length: 3.94 in
Width: 3.94 in
Height: 12.60 in
Weight: 0.729 kg

Adjustability

Fixed

Electric

System power: 7.5-24 W
Appliance Class: I

Protection

IP: 00