


Product data sheet

VEKTER 4 BOLLARD
VK-10011-W-W40
LIGMAN




- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Die-cast aluminium housing and extruded aluminium column pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency PMMA lens - Integral control gear

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	19.8 W	CRI	80
Total flux	2457 lm	LOR	100%
Luminous efficacy	124 lm/W	Total power	19.8 W

Light output 2 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	19.8 W	CRI	80
Total flux	2457 lm	LOR	100%
Luminous efficacy	124 lm/W	Total power	19.8 W

Mounting mode

Standing / Bollard

Shape and measurements

Length: 26.38 in
Width: 10.24 in
Height: 47.24 in
Weight: 11.2 kg

Adjustability

Fixed

Glare protection

Glare protection: UGR < 19

Electric

System power: 39.6 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Design

Color of housing: Black, White, Silver gray

Protection

IP: 65

IK: 08

Surface temperature: 40°C