Product data sheet

UNI-BRIGHT VISION ORIENT 3 ROUND - WW - B
ORR35B30
PROLED (MBN GMBH)



IP 20

Flexible surface-mounted luminaire with slim mounting housing - GU10 LED for replaceability and flexibility - Customizable with three decorative rings and honeycomb anti-glare cover.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	6 W	CRI	82
Total flux	730 lm	LOR	100%
Luminous efficacy	122 lm/W	Total power	6 W

Light output 2 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	6 W	CRI	82
Total flux	730 lm	LOR	100%
Luminous efficacy	122 lm/W	Total power	6 W

Light output 3 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	6 W	CRI	82
Total flux	730 lm	LOR	100%
Luminous efficacy	122 lm/W	Total power	6 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 4.92 in

Diameter: 9.84 in

Weight: 1.16 kg

Adjustability

Fixed, Rotatable, Tiltable

Electric

System power: 18 W

Appliance Class: I

Protection

IP: 20

Other operating numbers

Ambient temperature range: 14...113°F