Product data sheet


110 TUBEO LED TUBULAR LIGHT FITTING
110 15L100 DV P3X2,5 (11000 1010)
SCHUCH



IP 68 IK 07

LED tubular light fitting, TUBEO, 67 W, 10360 lm, 155 lm/W, Class I, IP68 (3m), IPX9K, symmetrical wide beam, 4000 K, CRI≥ 80, Ta -25 °C/+35 °C, L70>100000 h (@ Ta max), L80>70000 h (@ Ta max), L90>50000 h (@ Ta 25°C), Tube PMMA clear, Closure Stainless steel (1.4571), Through wiring (DV) 3x2.5 mm² PVC, stainless steel pipe clamps included, for unprotected outdoor areas. LED tubular light-fitting TUBEO with impact-resistant clear tube Ø 100mm, stainless steel locking caps, foamed silicone gasket and special element for length compensation. Powder-coated sheet steel reflector with Zhaga LED modules, frosted LED covers for glare limitation and ECG with overload and short circuit protection. Electrical connection by connection plug (FastConnect), male connector pre-installed, female with strain relief attached. Two stainless steel pipe clamps included. Resource-saving and environmentally friendly thanks to interchangeability of components (no disposable light fitting). Length 1700,00 mm, Width/Diameter 133,00 mm, Height 117,00 mm, Net weight 5,40 kg.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	67 W	CRI	80
Total flux	10360 lm	LOR	100%
Luminous efficacy	155 lm/W	ULOR	7%
		Total power	67 W

Mounting mode

Ceiling mounted, Wall mounted

Shape and measurements

Length: 66.93 in
Width: 5.24 in
Height: 4.61 in

Adjustability

Fixed

Electric

System power: 67 W
Appliance Class: I

Protection

IP: 68
IK: 07
Designation labels: CE