



# Product data sheet

LESS IS MORE 50  
312169.000.1  
RZB



Series: Less is more 50 Type of Protection: IP 20 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Housing: extruded anodised aluminium profile. End caps made of plastic, light-deflecting segments made of plastic (ABS) aluminium vapour-plated, highly polished, symmetrical beam, with diffuser made of plastic (PC) opal. Anodised aluminium ceiling canopy. 2 point steel cable suspension infinitely height adjustable. Converter included. Lamp (LED) included. Available Colours: anodised aluminium Type of Installation: Pendant Dimensions: L 1420, B 53, H 65 Lamp: LED Life time: 50000 h (L80/B10) Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 4650lm System power: 44W Beam Angle: 60°/59° Number of fittings B10A: 15 Number of fittings B16A: 24 Number of fittings C10A: 24 Number of fittings C16A: 40 Inrush current: 13A Unified Glare Ratio: 15,9 EEC: A+

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	44 W	CRI	80
Total flux	4650 lm	LOR	100%
Luminous efficacy	106 lm/W	Total power	44 W

## Mounting mode

Pendant

## Shape and measurements

Length: 2.09 in  
Width: 55.91 in  
Height: 2.56 in

## Adjustability

Fixed

## Electric

System power: 44 W

## Protection

IP: 20  
IK: 03