


Product data sheet

BRAGE L400 U 840
7018886
EXAKTOR



Brage är en effektiv underskåpsarmatur som finns i 3 olika längder, 400, 600 eller 1200. Armaturen har en väl avbländad ljusbild som passar för kök, sjukhus eller andra arbetsmiljöer. Brage är försedd med dubbla uttag samt vippströmbrytare som standard med undantag för Brage 400 som har ett enkelt uttag och vippströmbrytare. Armaturen finns i 3000K eller 4000K och som dimbar eller on/off. Armaturen monteras på undersidan av till exempel skåp eller hyllor och vid monteringen kan armaturens lock vändas så att uttaget placeras åt önskat håll. Armaturen tillverkas i Värnamo.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	4 W	CRI	80
Total flux	280 lm	LOR	100%
Luminous efficacy	70 lm/W	ULOR	67%
		Total power	4 W

Mounting mode

Ceiling mounted, Contact rail

Shape and measurements

Length: 15.75 in
Width: 3.35 in
Height: 1.69 in

Adjustability

Fixed

Electric

System power: 4 W
Ballast: ECG

Protection

IP: 21
Designation labels: CE

Other operating numbers

Ambient temperature range: -4...95°F