


Product data sheet

CORRF2 1X36W T26 HF E3 L840
96234477
THORN LIGHTING




A high performance IP65 dust and moisture resistant luminaire for aggressive atmospheres. For 1 x 36W T26 lamp(s) with electronic - fixed output circuit and integral 3 hour manual test emergency lighting function. Class I electrical. Canopy in light grey glass fibre reinforced polyester. Diffuser in acrylic with internal prisms. For surface or suspended mounting. Quick-fix installation brackets are supplied for surface mounting, optional accessory kits are available to help with other mounting options. Dimensions: 1294 x 112 x 112 mm Total power: 35.5 W Weight: 2.65 kg

Light output 1 (emergency)



1 x General service incandescent lamp			
Nominal lamp power	36 W	LOR	82%
Lamp flux	154 lm	ULOR	17%
Luminous efficacy	19 lm/W	Total flux	126 lm
CCT	3000 K	Total power	6.5 W
CRI	80		

Light output 2



1 x General service incandescent lamp			
Nominal lamp power	36 W	LOR	82%
Lamp flux	3350 lm	ULOR	17%
Luminous efficacy	77 lm/W	Total flux	2751 lm
CCT	3000 K	Total power	35.5 W
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 50.94 in
Width: 4.41 in
Height: 4.41 in
Weight: 2.7 kg

Electric

System power: 42 W
Voltage: 230-240 V AC
Appliance Class: I

Information regarding emergency functions

Supplementary emergency lighting
Emergency sign: N/A

Design

Material impression: Plastic

Protection

IP: 65

Designation labels: CE