

Product data sheet

STARGLASS FLOOR
D48 T
LUCEPLAN



IP
20

Il diffusore in vetro prismaticizzato stampato è capace di una brillante performance luminosa. Dispone di un accessorio antiabbagliamento.

Light output 1




1 x Halogen low voltage lamp without reflector

Nominal lamp power	205 W	Socket	E27
Lamp flux	2520 lm	LOR	67%
Luminous efficacy	7 lm/W	ULOR	6%
CCT	2821 K	Total flux	1695 lm
CRI	99	Total power	250 W



1 x Halogen low voltage lamp without reflector

Nominal lamp power	140 W	Socket	E27
Lamp flux	2840 lm	LOR	67%
Luminous efficacy	8 lm/W	ULOR	6%
CCT	3000 K	Total flux	1910 lm
CRI	99	Total power	250 W



1 x Halogen low voltage lamp without reflector

Nominal lamp power	105 W	Socket	E27
Lamp flux	1980 lm	LOR	67%
Luminous efficacy	5 lm/W	ULOR	6%
CCT	3000 K	Total flux	1332 lm
CRI	99	Total power	250 W

Mounting mode

Standing / Bollard

Electric

System power: 250 W

Shape and measurements

Length: 20.40 in

Width: 20.45 in

Height: 79.82 in

Adjustability

Fixed

Protection

IP: 20