

Product data sheet

EPSYLON - POLE TOP LIGHT / DOUBLE HEAD


7236-0-5-876-XX

UNILAMP




EPSYLON is the family of pole top and wall mount luminaires with unshielded symmetrical distribution. The recommended mounting height is between 3 – 5 meters. To avoid discolouration of the lens we have used a high quality PMMA clear cover. The diffuser gives a broad spread light distribution. These luminaires are generally used to illuminate gardens, parks, pedestrian, squares and open spaces. They are assembled with high brightness multiple LEDs. Aluminium pole, galvanized steel pole, pole adaptor and anchorage unit for concrete foundation are also available. • Designed, Manufactured and Tested according to IEC 60598-1, IEC 60598-2-1 and VDE regulations. • LM6 Die Cast Aluminium and Spun Aaluminium body. • Stainless steel screws. • Nano Ceramic surface conversion. • Double layer coating. • Clear PMMA diffuser. • Post-cured silicone gasket. • High quality LED module and driver. • GFR PA6.6 Terminal block. • M20 cable gland or TPE grommet. • Pole light pre-wired with outdoor cable. • Installation work has to be carried on according to the enclosed product manual.

Light output 1



1 x LED			
Nominal lamp power	26 W	LOR	77%
Lamp flux	3800 lm	ULOR	5%
Luminous efficacy	146 lm/W	Total flux	2928 lm
CCT	4000 K	Total power	29 W
CRI	80		

Light output 2



1 x LED			
Nominal lamp power	26 W	LOR	77%
Lamp flux	3800 lm	ULOR	5%
Luminous efficacy	146 lm/W	Total flux	2928 lm
CCT	4000 K	Total power	29 W
CRI	80		

Mounting mode

Pole top mounted

Shape and measurements

Length: 24.03 in

Width: 58.26 in

Height: 34.02 in

Electric

System power: 58 W

Controller: DALI

Appliance Class: I

Adjustability

Fixed

Protection

IP: 54

IK: 06