Product data sheet


LADOR 10 SURFACE EXTERIOR DOWNLIGHTS
LD-80011-E-8030
LIGMAN



IP 65 IK 07

- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000K - Die-cast aluminium housing - Pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Stainless steel fasteners in grade 304 with zinc flake coating (ZFC) - Durable silicone rubber gasket - Clear toughened glass - High-efficiency PMMA lens - Integral control gear

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	10 W	CRI	80
Total flux	998 lm	LOR	100%
Luminous efficacy	100 lm/W	ULOR	100%
		Total power	10 W

Mounting mode

Ceiling mounted, Wall mounted

Shape and measurements

Length: 3.23 in
Width: 3.23 in
Height: 4.65 in
Weight: 1.1 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 10 W
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 65
IK: 07
Surface temperature: 40°C