



Product data sheet

SAFESITE LED LINEAR TOP CONDUIT 6950 LUMENS, 4 FOOT, WIDE DISTRIBUTION, CLEAR POLYCARBONATE LENS
LHF4WN27DXXXXN
DIALIGHT



SafeSite LED Linear Top Conduit 6,950 Lumens 52 Watts 100-277V AC Neutral White, 80CRI Clear Polycarbonate Lens 4 Foot Length CID2 Groups A, B, C & D CIIID1 Groups E, F & G CIIID2 Groups F & G CIII UL 844 UL 1598/A CSA C22.2 No. 137 CSA C22.2 No. 250 NEMA 4X 2000 PSI Hose-down rating Wide Distribution IP66/67 Scaled IES File

Light output 1 (integrated)



Lamp type	LED	CCT	3783 K
Nominal lamp power	52.2 W	CRI	80
Total flux	6950 lm	LOR	100%
Luminous efficacy	133 lm/W	Total power	52.2 W

Mounting mode

Pendant

Shape and measurements

Length: 5.00 in
Width: 48.03 in
Height: 6.18 in

Adjustability

Rotatable, Tilttable

Electric

System power: 52.2 W
Voltage: 120 V AC, 230 V AC, 240 V AC, 277 V AC
Appliance Class: I

Protection

IP: 66
IK: 10