Product data sheet


FORREY 19 WALL LUMINAIRES
FOR-30042-T5-W40
LIGMAN



IP 65 IK 08

- Lamp COB - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Die-cast aluminium housing and frame pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Opal, impact-resistant, UV-stabilised polycarbonate diffuser - Models with shade will have colour white coating at inside of shade luminaire and outside surface coating according to the colour of luminaire - Integral control gear

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	69.6 W	CRI	80
Total flux	6428 lm	LOR	100%
Luminous efficacy	92 lm/W	ULOR	100%
		Total power	69.6 W

Mounting mode

Wall mounted

Shape and measurements

Height: 27.83 in
Diameter: 34.65 in
Weight: 8.9 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 69.6 W
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 65
IK: 08
Surface temperature: 40°C