Product data sheet


LUMINAIRES WITH UV RECIRCULATION
V1-C0-0UV70-10PRD-4003065 UV 070 IP40 RECESSED 30W 6500K PRISM DALI
VARTON



IP 40 IK 03

LED luminaire combined with a UV recirculator. Material: Stainless steel housing with white powder coating. Application: administrative facilities, healthcare, educational facilities, industrial facilities. Installation: recessed, compatible with the Armstrong Prelude 24 suspended ceiling systems. Input voltage (AC, 50Hz), V: 176...264 AC frequency, Hz: 50 Flicker, %: 2 Climatic modification and category of placement: УХЛ4 Color rendering index: 80-89 Protection class: I Mounting method: Built-in Ingress protection (IP): IP40 Radiation angle, °: 120 Impact resistance: IK03 Power factor: 0,95 https://www.varton.ru/products/uf-obluchateli/uv-bakteritsidnye-svetilniki/uv-070-595-595-126-mm-ip40-vstraivaemye/svetodiodnyy-svetilnik-varton-s-uv-blokom-vstraivaemyy-30-vt-595kh595kh126-mm-6500-k-ip40-s-prizmati_2/

Light output 1



1 x LED

Nominal lamp power	30 W	LOR	100%
Lamp flux	3800 lm	Total flux	3800 lm
Luminous efficacy	127 lm/W	Total power	30 W
CCT	6500 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 23.43 in
Width: 23.43 in
Height: 4.96 in

Adjustability

Fixed

Electric

System power: 30 W

Protection

IP: 40
IK: 03