


# Product data sheet

C95-W450X450 LED 2500 830 OP  
GLAMOX




IP  
40

IK  
07

Light source LED: 700-2500lm out. 3000/4000K, CRI 80. MacAdams 3. Lifetime LED: Up to 100.000h Ta25. Minimum 50 000h Max Ta. For precise technical information please see the data sheet on item level. (Use <Find your version> on right side) Driver HF or DALI. Driver life time up to 100.000 h/10 % (max failure) at Ta 25°C. Body material & colour Body frame in anodized aluminum or white anodized aluminum with steel plate on back. Mounting Mounted direct to the wall thru 4 mounting key holes on top. Can also be surfaced mounted in the ceiling. Connection Cable entry on back. 3 or 5 pole push-in terminal block. Optics Opalic diffusor (OP) Emergency system Only on 450x450. Standard (S), Self test (ST) or DALI. 1h or 3h.

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	22 W	CRI	80
Total flux	2304 lm	LOR	100%
Luminous efficacy	105 lm/W	ULOR	84%
		Total power	22 W

## Mounting mode

Wall mounted

## Shape and measurements

Length: 17.48 in

Width: 17.48 in

Height: 2.05 in

## Adjustability

Fixed

## Electric

System power: 22 W

## Protection

IP: 40

IK: 07