


Product data sheet

BTECM L13 LE3
BTEC EMERGENCY
DEXTRA




Btec Large Downlighter - Ø220mm, IP40 Recessed downlighter with spun aluminium housing, spring steel retaining clips and high transmission polycarbonate diffuser. Options: LE3 - Lithium Emergency (493 lumen output) LS3 - Lithium Selftest LA3 - Lithium Autotest CB - Please specify 50v, 110v or 230v when ordering S - Switch Dimming D - Digital Dimming (DSI) A - Digital Addressable Lighting Interface (DALI) C - Bi-Level Dimming (Corridor Function)

Light output 1 (integrated, emergency)



Lamp type	LED	CCT	4000 K
Nominal lamp power	3 W	CRI	80
Total flux	476 lm	LOR	100%
Luminous efficacy	159 lm/W	Total power	3 W

Light output 2 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	9.1 W	CRI	80
Total flux	1103 lm	LOR	100%
Luminous efficacy	121 lm/W	Total power	9.1 W

Mounting mode

Ceiling recessed

Shape and measurements

Height: 2.56 in
Diameter: 6.57 in

Adjustability

Fixed

Electric

System power: 12.1 W
Ballast: ECG

Information regarding emergency functions

Supplementary emergency lighting
Emergency sign: N/A

Protection

IP: 20
Designation labels: CE