
Product data sheet


LUCAS IV (WALL FITTING) 9.834.2152.15 LEIPZIGER LEUCHTEN






Mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets -Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x High pressure sodium vapour lam	р
-------------------------------------	---

50 W	LOR	84%
3500 lm	Total flux	2932 lm
47 lm/W	Total power	62 W
2000 K		
25		
	3500 lm 47 lm/W 2000 K	3500 lmTotal flux47 lm/WTotal power2000 K



1 x High	pressure	sodium	vanour	lamn
T A LIIGH	pressure	Souran	vapour	ianip

70 W	LOR	84%
5600 lm	Total flux	4691 lm
57 lm/W	Total power	83 W
2000 K		
25		
	5600 lm 57 lm/W 2000 K	5600 lmTotal flux57 lm/WTotal power2000 K

Mounting mode	Electric
Wall mounted	System power: 62-83 W
Shape and measurements	Protection
Height: 22.44 in	IP: 55
Diameter: 22.44 in	