Product data sheet


MELBOURNE 6 IN-GROUND LUMINAIRES
MEL-60051-E-8040
LIGMAN



IP 67 IK 10

- Lamp COB - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000K Stainless steel body in grade 316 - Pre-treated before powder coating ensuring highcorrosion resistance - Front ring in grade 316 stainless steel - Adjustable: Tilt 25°, Rotation 360° for ME-60051,ME-60052, ME-60053, ME-60061, ME-60062,ME-60063 - Single cable entry, through wiring upon request - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency PMMA lens - Clear or frosted toughened glass - Integral control gear - Recessing box in high-density PA66 with 30glass fibers included - Suitable for drive-over with a maximum load of5000 kg - Vehicles with pneumatic tires can drive over theluminaire but the speed must not exceed 50 km/h - Load is transferred by the housing to thefoundation - The distance between the luminaire and theilluminated surface should be at least 0.5 m

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	19.9 W	CRI	80
Total flux	2019 lm	LOR	100%
Luminous efficacy	101 lm/W	ULOR	100%
		Total power	19.9 W

Mounting mode

Standing / Bollard, Floor recessed

Shape and measurements

Height: 10.63 in
Diameter: 8.46 in
Weight: 11 kg

Adjustability

Fixed

Electric

System power: 19.9 W
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 67
IK: 10
Surface temperature: 40°C