Product data sheet


ANDHO MIDI
931196.002.76
RZB



IP 65 IK 08

Series: ANDHO midi High-quality surface-mounted downlight for indoor and outdoor use. Housing made of corrosion-resistant die-cast aluminium, seawater-resistant powder-coated (C4, in accordance with ISO 12944-6). C5 coating available on request. With membrane valve as a standard to avoid condensed water. Cover clear single-pane toughened glass. Rotation-symmetric reflector made of reflex-boosted MIRO-SILVER. Easy installation with a separate ceiling frame and plug connection. 5 pole double terminal for through-wiring. Colour: traffic white, matt (RAL 9016) Diameter: 154 mm Height: 157 mm Lamp: LED Socket: without socket Colour temperature: 3000K Colour rendering index (CRI): 80 System power: 15 W Rated luminous flux: 2000 lm Beam angle Down: 63° Luminous efficiency: 133 lm/W Control gear: Converter, dimmable, DALI Protection class: I Type of protection: IP 65

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	15 W	CRI	80
Total flux	2000 lm	LOR	67%
Luminous efficacy	133 lm/W	ULOR	14%
		Total power	15 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 6.18 in
Diameter: 6.06 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 15 W

Protection

IP: 65
IK: 08